

## PRODUCT FICHE



**Kitchen hood  
200006  
CW4951S**
**USP :**

Product group	Hood
Image	
Surface material	Stainless steel and glass
Colour	Stainless steel and black glass
Max. noise level	60 dB(A)re 1 pW
Number of speed positions	4 venting speeds
Filter material	Aluminium
Control setting	Touch control
Illumination	Halogen lightning: 2 × 20 W
No return airflow flap	150 mm
Grease filter indicator	✓
Timer function	✓
Dishwasher safe grease filters	✓
Max. noise level	60 dB(A)re 1 pW

**Basic information :**

Product group	Kitchen hood
Decor panel options	/
Construction type	Free-standing
Brand	ASKO
Product name / Family	Kitchen hood
Commercial code	CW4951S
Internal article number	200006
EAN code	7392417042944
Color body	/
Material body	Stainless steel/glass
Color chimney	Inox
Material chimney	Stainless steel
Typology	Decorative
Installation type	Wall freestanding
Motor location	Integrated in decorative chimney
Operating mode	Convertible
Connection Rating	248 W
Current	10 A
Voltage	220-240
Frequenc	50
Approval certificates	/
Length of electrical supply cord	160 cm
Plug type	Euro
Height of the chimney (mm)	525/1045
Height of product, without chimney	70 mm
Net weight	20,5 Kg
Gross weight	23,0 Kg
Width of the product	900 mm
Height of the product	70 mm
Depth of the product	480 mm
Width of the packed product	950 mm
Height of the packed product	450 mm
Depth of the packed product	550 mm
Air exhaust	Yes

**Features :**

Remote control	/
Short description of the product	CW4951S
Type of control	Electronic
Type of manual control devices	Touch control
Number of motors	1
Total power of the motors	198 W
Number of speed settings	4
Boost position	Yes

Maximum output air extraction	<b>650 m³/h</b>
Maximum output recirculating air	/
Illumination setting	<b>ON/OFF</b>
Number of lights	<b>2</b>
Type of lamps used	<b>Halogenous</b>
Total power of the lamps	<b>40 W</b>
Max. noise level	<b>60 dB(A) re 1 pW</b>
Diameter of air outlet	<b>150</b>
No-return airflow flap	<b>Yes</b>
Grease filter material	<b>Washable aluminium</b>
Odour filter	<b>No</b>

### Energy label information / Performance :

Air flow at intensive or boost setting	/
Maximum Air flow	<b>650 m³/h</b>
Minimum air flow	/
Total annual energy consumption	/
Energy efficiency class	/
Fluid Dynamic Efficiency class	/
Grease filtering efficiency class	/
Lighting efficiency	/
Noise level with boost position	/
Sound power at max. speed	<b>60 dB</b>
Sound power at min. speed	/
Maximum extraction rate by extraction operation	<b>650 m³/h</b>
Energy efficiency index (2010/30/EC)	<b>0,0 %</b>
Fluid Dynamic Efficiency (2010/30/EC)	<b>0,0</b>
Grease filtering efficiency (2010/30/EC)	/
Lighting efficiency (2010/30/EC)	<b>0,0</b>
Noise level with boost position	/
Power consumption in standby mode (2010/30/EC)	/
Power consumption in off-mode - NEW (2010/30/EC)	/

