1/2

PRODUCT FICHE

Appliance status: R Valid from: 24.2.2017 Last modification: 26.4.2019 23:32:16



Hob 568452 HIG1944MF

USP:

Product group	Hob
Image	
Auto pan detection	✓
Bridge Zone technology	✓
Pause function	✓
Fusion Volcano Wok burner	✓
Central switch off	✓
Overheating switch off	✓
Cooking time limiter	✓
Flame failure protection	✓

Basic information:

Product group	Hob
Brand	ASKO
Product name / Commercial code	HIG1944MF
Commercial code	568452
EAN code	3838942164811
Construction type	Built-in
Control type	Mechanical
Energy input	Electricity
Total number of positions that can be used at the same time	1
Number of gas burners	1
Number of electric cooking zones	I
Number of electric plates	1
Number of radiant plates	1
Number of halogen plates	1
Number of induction plates	I
Number of electric warming zones	1
Location of control panel	Hob front
Basic external material of hob surface	1
Hob color	I
Hob frame material	1
Hob edges	1
Electrical connection rating	7400 W
Gas connection rating	I
Current	1
Current Voltage	/ 220-240
Voltage	220-240
Voltage Frequency	220-240 /
Voltage Frequency Marks of conformity	220-240 / GSC,RCM
Voltage Frequency Marks of conformity Plug type	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm
Voltage Frequency Marks of conformity Plug type Width of the product	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm 522 mm
Voltage Frequency Marks of conformity Plug type Width of the product Height of the product	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm
Voltage Frequency Marks of conformity Plug type Width of the product Height of the product Depth of the product	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm 522 mm
Voltage Frequency Marks of conformity Plug type Width of the product Height of the product Depth of the product Width of the packed product	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm 522 mm 930 mm
Voltage Frequency Marks of conformity Plug type Width of the product Height of the product Depth of the product Width of the packed product Height of the packed product	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm 522 mm 930 mm 230 mm
Voltage Frequency Marks of conformity Plug type Width of the product Height of the product Depth of the product Width of the packed product Height of the packed product Depth of the packed product	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm 522 mm 930 mm 230 mm 600 mm
Voltage Frequency Marks of conformity Plug type Width of the product Height of the product Depth of the product Width of the packed product Height of the packed product Holph of the packed product Min height of installation niche	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm 522 mm 930 mm 230 mm 600 mm /
Voltage Frequency Marks of conformity Plug type Width of the product Height of the product Uppth of the product Width of the packed product Height of the packed product Height of the packed product Height of installation niche Max height of installation niche	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm 522 mm 930 mm 230 mm 600 mm / 54 mm / 860 mm
Voltage Frequency Marks of conformity Plug type Width of the product Height of the product Uppth of the product Width of the packed product Width of the packed product Height of the packed product Height of installation niche Max height of installation niche Min width of installation niche	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm 522 mm 930 mm 230 mm 600 mm / 54 mm / 860 mm 490 mm
Voltage Frequency Marks of conformity Plug type Width of the product Height of the product Depth of the product Width of the packed product Height of the packed product Height of installation niche Max height of installation niche Max width of installation niche Max width of installation niche	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm 522 mm 930 mm 230 mm 600 mm / 54 mm / 860 mm
Voltage Frequency Marks of conformity Plug type Width of the product Height of the product Depth of the product Width of the packed product Height of the packed product Height of installation niche Max height of installation niche Max width of installation niche Depth of installation niche Depth of installation niche Depth of installation niche	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm 522 mm 930 mm 230 mm 600 mm / 54 mm / 860 mm 490 mm
Voltage Frequency Marks of conformity Plug type Width of the product Height of the product Depth of the product Width of the packed product Height of the packed product Height of installation niche Max height of installation niche Max width of installation niche Depth of installation niche Max width of installation niche Depth of installation niche Net weight	220-240 / GSC,RCM Without plug and supply cord 904 mm 60 mm 522 mm 930 mm 230 mm 600 mm / 54 mm / 860 mm 490 mm 18,5 kg

Features:

2/2

Short description of the product	IG9BB02IFA - HIG1944MF
Automatic programmes	No
Location of 1st heating element	1
Type of 1st heating element	1
Dimension of 1st heating element	1
Power of 1st heating element	1
Power on indicator	1
Plate on indicator	1
Type of lid	None
Residual heat indicator	1
Main on/off switch	No
Accessories included	
Electronic timer	No

