

## PRODUCT FICHE



### Kitchen hood 511990 CW4938G

#### USP :

Product group	Hood
Image	
Surface material	Stainless steel/painted steel
Max. noise level	62 dB(A)re 1 pW
Number of speed positions	9
Filter material	Stainless steel grease filter
Control setting	Touch control
Illumination	Led strip: 2 × 3 W
No return airflow flap	150 mm
Grease filter indicator	✓
Timer function	✓
Dishwasher safe grease filters	✓
Max. noise level	62 dB(A)re 1 pW

#### Basic information :

Product group	Kitchen hood
Decor panel options	/
Construction type	Free-standing
Brand	ASKO
Product name / Family	Kitchen hood
Commercial code	CW4938G
Internal article number	511990
EAN code	3838942065613
Color body	/
Material body	Stainless steel/painted steel
Color chimney	Inox
Material chimney	Stainless steel/glass
Typology	Decorative
Installation type	Wall freestanding
Motor location	Motor integrated in the hood
Operating mode	/
Connection Rating	242 W
Current	/
Voltage	220-240
Frequenc	50/60
Approval certificates	CE
Length of electrical supply cord	150 cm
Plug type	AUS
Height of the chimney (mm)	627/1172
Height of product, without chimney	85 mm
Net weight	32,0 Kg
Gross weight	41,5 Kg
Width of the product	898 mm
Height of the product	85 mm
Depth of the product	534 mm
Width of the packed product	978 mm
Height of the packed product	585 mm
Depth of the packed product	560 mm
Air exhaust	/

#### Features :

Remote control	/
Short description of the product	WS90ENTEE-CW4938G
Type of control	Electronic
Type of manual control devices	Touch control
Number of motors	1
Total power of the motors	230 W
Number of speed settings	9
Boost position	Yes
Maximum output air extraction	793 m³/h

Maximum output recirculating air	535 m <sup>3</sup> /h
Illumination setting	Steps
Number of lights	2
Type of lamps used	LED stripe
Total power of the lamps	6 W
Max. noise level	62 dB(A) re 1 pW
Diameter of air outlet	/
No-return airflow flap	Yes
Grease filter material	Washable stainless steel
Odour filter	No

### Energy label information / Performance :

Air flow at intensive or boost setting	/
Maximum Air flow	793 m <sup>3</sup> /h
Minimum air flow	238 m <sup>3</sup> /h
Total annual energy consumption	46,9 kWh/year
Energy efficiency class	A
Fluid Dynamic Efficiency class	A
Grease filtering efficiency class	A
Lighting efficiency	A
Noise level with boost position	66 dB
Sound power at max. speed	62 dB
Sound power at min. speed	40 dB
Maximum extraction rate by extraction operation	793 m <sup>3</sup> /h
Energy efficiency index (2010/30/EC)	54,6 %
Fluid Dynamic Efficiency (2010/30/EC)	38,7
Grease filtering efficiency (2010/30/EC)	62,1 %
Lighting efficiency (2010/30/EC)	35,8
Noise level with boost position	/
Power consumption in standby mode (2010/30/EC)	/
Power consumption in off-mode - NEW (2010/30/EC)	/

